

# Flexible & Affordable

The Sicur Anchor Safety System is designed to minimise the distance and consequences of a fall when a worker is attached to it. It is designed to be used on surfaces up to a 5 degree pitch and is simple and straightforward to use, allowing you to get the job done both quickly and safely.


A simple, straightforward safety solution without any risk of endangerment, the Sicur Anchor Safety System is the perfect solution to a range of tasks where safety is paramount.

The Sicur Anchor Safety System consists of a set of non-penetrative weights assembled into a single, round unit.

Working in conjunction with our roof post, we create a powerful friction anchor on the roof that is more than capable of withstanding a fall. The unit has also been specifically designed to reduce trip hazards and to occupy as small a space as possible on the roof: it's no more than 1200 mm wide.

Suitable for the full range of flat roofs (up to a maximum of 5° pitch), this system has been tested on a range of substrates including concrete, asphalt and single ply membrane.

Its quality has also been assured by external means, and it is fully tested in compliance with **EN 795:2012 class E**. With its competitive pricing and high recycled material content, it's kind to both your wallet and the environment.



## Key Features

- > **Small but substantial product: a minimal trip hazard**
- > **Easy to assemble and store when not in use**
- > **Non-penetrative: ideal for older buildings**
- > **Usable on flat roofs no steeper than a 5° pitch**
- > **Tested on a wide range of roofs and materials**
- > **Competitively priced... without any compromise in quality**
- > **Environmentally friendly**

**Safety should be the priority of anyone working at height, but sometimes you need a smaller problem rectifying without wanting to put an extensive and time-consuming set of safety measures in place.**